

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Sta'-Put S200 Aerosol Adhesive

GENERAL USE: Suitable in woodworking, manufactured housing, general construction, recreational vehicle, marine, furniture, textile, HVAC, upholstery, and other porous or non-porous surfaces where a permanent bond is required.

MANUFACTURER

ITW TACC
 56 Air Station Industrial Park
 Rockland MA 02370
Product Stewardship: (781) 878-7015
Service Number: (800) 503-6991

DISTRIBUTOR

Alfa-Pak
 Unit 1, 100 Beresford Road
 Lilydale Victoria 3140
Emergency Contact: (03) 9735-9133

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

COMMENTS: STA'-PUT is a registered trademark of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"F+" - Extremely flammable
 "Xn" - Harmful

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Contains methylene chloride which is a nonflammable liquid with a mildly sweet odor.

IMMEDIATE CONCERNS: HAZARDOUS SUBSTANCE. DANGEROUS GOODS. Extremely flammable vapor. Vapors may cause flash fire and explosion. Contents under pressure. Harmful or fatal if swallowed. Vapors may cause dizziness, headache, nausea, drowsiness, unconsciousness and respiratory irritation. Contains methylene chloride which is harmful if inhaled. Can also cause skin and eye irritation. Methylene Chloride is a possible cancer hazard. May cause cancer based on animal data.

POTENTIAL HEALTH EFFECTS

EYES: Can cause moderate to severe eye irritation with temporary damage possible.

SKIN: Prolonged or repeated contact of liquid can cause irritation, defatting of skin, and dermatitis. Prolonged single exposure can result in a progressively severe burning sensation or redness.

SKIN ABSORPTION: Can be absorbed through the skin but not in sufficient amounts to cause adverse effects.

INGESTION: Harmful or fatal if swallowed. Can cause gastrointestinal irritation with symptoms of nausea, vomiting and diarrhea.

INHALATION: Inhalation is the major potential route of exposure. Exposure to high concentrations of vapor or mist can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure. Exposure

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

to high concentrations can cause irregular heartbeat, cardiac arrest and death. Overexposure has been shown to cause adverse effects on the lungs, liver, kidney, nervous system and internal organs. Carboxyhemoglobin levels can be elevated in persons exposed to methylene chloride and can cause a substantial stress on the cardiovascular system.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Mild to moderate skin irritant.

SKIN ABSORPTION: Can be absorbed through the skin but not in sufficient amounts to cause adverse effects.

INGESTION: Ingestion of this material can cause mouth, throat, esophageal, and gastrointestinal tract irritation.

INHALATION: Exposure to high concentrations of vapor or mist can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure. Exposure to high concentrations can cause irregular heartbeat, cardiac arrest and death. Overexposure has been shown to cause adverse effects on the lungs, liver, kidney, nervous system and internal organs.

CHRONIC EFFECTS: Prolonged overexposure has caused toxic effects on the liver and kidneys.

CARCINOGENICITY: Carcinogen Category 3 (HSIS)

MUTAGENICITY: None known.

REPRODUCTIVE TOXICITY

REPRODUCTIVE EFFECTS: None known.

TERATOGENIC EFFECTS: None known.

MEDICAL CONDITIONS AGGRAVATED: Alcoholism, acute and chronic liver and kidney disease, chronic lung disease, anemia, coronary disease or rhythm disorders of the heart. Exposure can result in cardiac sensitization and increase the risk of cardiac arrest.

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, and Skin Contact

TARGET ORGAN STATEMENT: Central Nervous System (CNS)

CANCER STATEMENT: Methylene chloride has caused cancer in certain laboratory animal tests. IARC has classified methylene chloride in Group 2B as a substance considered possibly carcinogenic to humans.

IRRITANCY: Eyes, nose, throat, respiratory tract, and skin irritation.

COMMENTS: EU Risk & Safety Phrases

R: 12-40

S: (2)-9-16-23-24/25-36/37

3. COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

Chemical Name	Wt.%	CAS	EINECS	Classification
Hydrocarbon Propellant	25 - 50	Mixture	200-338-0	F+; 12
Methylene Chloride	45 - 70	000075-09-2	2008389	Xn; 40

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

INGESTION: Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: -104°C (-156°F)

FLAMMABLE LIMITS: 1.8 to 9.5

AUTOIGNITION TEMPERATURE: (788°F) to (1033°F)

FLAMMABLE CLASS: Class IA

GENERAL HAZARD: Extremely Flammable. Under Pressure.

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide, water spray or fog.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Aldehydes

EXPLOSION HAZARDS: Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

SENSITIVITY TO IMPACT: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

6. ACCIDENTAL RELEASE MEASURES

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
MSDS No: JSP-0290 Australia
Date Revised: 12/17/2009
Revision No: 4

Sta'-Put S200 Aerosol Adhesive

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

HANDLING: Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

STORAGE: Keep container closed when not in use. Store in a dry well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: 9 months from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Hydrocarbon Propellant	TWA	1000 ppm	1800 mg/m ³	800 ppm	NL
	STEL	NL ^[1]	NL ^[1]	NL ^[1]	NL ^[1]
Methylene Chloride	TWA	25 ppm ^[2]	NL ^[2]	50 ppm	174 mg/m ³
	STEL	125 ppm	NL	NL ^[1]	NL ^[1]
Footnotes: 1. NL = Not Listed 2. OSHA limits per 29 CFR 1910.1052					

ENGINEERING CONTROLS: Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) or a full face respirator.

SKIN: Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PROTECTIVE CLOTHING: Wear chemical resistant gloves, such as nitrile rubber.

WORK HYGIENIC PRACTICES: Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Aerosol

ODOR: Mildly sweet odor

COLOR: Clear or Red

pH: Not Available

PERCENT VOLATILE: 84.9

Notes: by weight

VAPOR PRESSURE: Not Available

VAPOR DENSITY: Not Available

MATERIAL SAFETY DATA SHEET

Date Issued: 12/17/2009
MSDS No: JSP-0290 Australia
Date Revised: 12/17/2009
Revision No: 4

Sta'-Put S200 Aerosol Adhesive

BOILING POINT: -24.4°C (-12°F) to -41.8°C (-43.2°F)

FREEZING POINT: Not Available

MELTING POINT: Not Available

POUR POINT: Not Available

FLASHPOINT AND METHOD: -104°C (-156°F)

SOLUBILITY IN WATER: Slight

EVAPORATION RATE: > 1.0 (n-Butyl Acetate=1)

DENSITY: 840.8 gr/L

PARTICLE SIZE: Not Available

SPECIFIC GRAVITY: 0.841

VISCOSITY: Not Available

MOLECULAR WEIGHT: Not Available

(VOC): 294.400 gr/L

OXIDIZING PROPERTIES: None known.

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable.

POLYMERIZATION: Product will not undergo polymerization.

CONDITIONS TO AVOID: Avoid fire, sparks, static electricity and hot surfaces.

POSSIBILITY OF HAZARDOUS REACTIONS: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong acids and strong bases.

11. TOXICOLOGICAL INFORMATION

ACUTE

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Hydrocarbon Propellant	No data	No data	No data
Methylene Chloride	1500 to 2500 mg/kg	No data	14400 ppm (7-hr dose - mouse)

CARCINOGENICITY

Chemical Name	IARC Status
Methylene Chloride	2B

IARC: Group 2B Animal Carcinogen

Notes: Carcinogen Category 3 (HSIS)

IRRITATION: Eyes, nose, throat, respiratory tract irritation.

CORROSIVITY: Not Applicable

SENSITIZATION: Not Applicable

NEUROTOXICITY: Not Applicable

GENETIC EFFECTS: Not Applicable

REPRODUCTIVE EFFECTS: Laboratory animal studies on mice, rats and rabbits have been conducted to evaluate the potential reproductive and developmental effects of methylene chloride exposures. Methylene chloride exposure has not been shown to cause teratogenic effects (birth defects) in experimental animals.

MUTAGENICITY: Methylene chloride has been evaluated for its potential to induce genotoxic effects in both in vivo and in vitro systems with mixed results. Based on this evidence, methylene chloride exposure may be considered to be a weak mutagen in mammalian systems.

GENERAL COMMENTS: Inhalation is the major potential route of entry

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Methylene chloride is expected to evaporate rapidly from both water and near-surface soil.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

DISTRIBUTION: Not Available

AQUATIC TOXICITY (ACUTE): Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Liquified Gas, Flammable, N.O.S.

PRIMARY HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: 3161

PACKING GROUP: NA

NAERG: 115

MARINE POLLUTANT #1: None

OTHER SHIPPING INFORMATION: contains (Propane, n-Butane, Dichloromethane)

SPECIAL SHIPPING NOTES: If individual container size is less than 1.3 gallons, the proper shipping name is:

ORM-D Consumer Commodity
 Non-Regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes **PRESSURE GENERATING:** Yes **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Methylene Chloride	45 - 70	000075-09-2

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Methylene Chloride	45 - 70	2200 kg

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Hydrocarbon Propellant	Mixture
Methylene Chloride	000075-09-2

CLEAN AIR ACT

Chemical Name	Wt. %	CAS
Methylene Chloride	45 - 70	000075-09-2

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
 MSDS No: JSP-0290 Australia
 Date Revised: 12/17/2009
 Revision No: 4

Sta'-Put S200 Aerosol Adhesive

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Hydrocarbon Propellant	New Jersey Right to Know List Pennsylvania Right to Know List
Methylene Chloride	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION



"F+" - Extremely flammable



"Xn" - Harmful

16. OTHER INFORMATION


INFORMATION CONTACT: (781) 878-7015

REVISION SUMMARY: Revision #: 4 This MSDS replaces the December 12, 2008 MSDS. Any changes in information are as follows: In Section 1 General Use Statement Date Prepared CHEMTREC MSDS In Section 2 Emergency Overview - Immediate Concerns Medical Conditions Aggravated Comments Reproductive Toxin Carcinogenicity In Section 9 Odor (Group Field) for pH (Group Field) for Vapor Pressure (Group Field) for Vapor Pressure Density (Group Field) for Freezing Point (Group Field) for Melting Point Density (lbs) Particle (Unit) (Group Field) for Viscosity (Group Field) for Molecular Comments Oxidizing Properties (Group Field) for Pour Point In Section 11 Carcinogenicity Toxicological In Section 12 Environmental Data Aquatic Toxicity (Acute) Distribution

HMIS RATING

HEALTH:	*	2
FLAMMABILITY:		4
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:	B	

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children

For professional or industrial use only

If you cannot read, or do not understand all directions, cautions, and warnings, do not use this product

For spray applications, use only with approved equipment

MATERIAL SAFETY DATA SHEET



Date Issued: 12/17/2009
MSDS No: JSP-0290 Australia
Date Revised: 12/17/2009
Revision No: 4

Sta'-Put S200 Aerosol Adhesive

MANUFACTURER DISCLAIMER:

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW TACC. The data on this sheet relates only to the specific material designated herein. ITW TACC assumes no legal responsibility for use or reliance upon these data.